

M-304/MZ-393 Pan/Tilt series

Features:

- Aluminum structure,water-proof,heat-resistant,corrosion-resistant
- Professional wiring design to prevent wire disorder,save wires
- Magnetic synchronized motor, pan/tilt operation more reliable
- MP304 is presetable,32presets positions,MD304 with decoder
- Protocol pelco,AD etc
- Housing ME515,ME512,ME310 are compatible options
- 3 models available



Specifications & Quotations

Model	MZ-304	MD-304	MP-304
Power/comsumption	AC24V/30W, AC22V/50W(with heater)		
Active angel	Pan: 0~355° adjustable, Tilt: 6~90° unadjustable		
Speed	Pan: 7.5°/S, Tilt: 6°/S		
Built-in decoder	NO	YES	YES
Preset point	NO	NO	32
Protection Grade	IP66		
Max. loading& capacity	10kg, 4.2kg		
Operating temperature	-20°C-65°C, -40°C-65°C(with heater)		
Dimension& weight	189x169x222mm, 4.2kg(without housing)		

Features:

- Cables for camera and lens connection through the inside of pan/tilt
- No disorderly cable



Specifications & Quotations

Model	MZ-393
Power	AC24V/ 10W(with heater)
Application	Indoor walling
Horizontal turning angel	0~350° adjustable,
Upright turning angel	10~60° unadjustable
Speed	Pan: 5.3°/S, Tilt: 2.8°/S
Material	Enhanced anti-burning ABS
Dimension& weight	274X132X127mm, 1.4kg

